

Technical Data Sheet

Pareo Zero

Finish for Wooden Decks & Sidings

Oil emulsion for the protection of decks, sidings, fences and other outdoor wood projects. Does not peel or blister. Prevents weathering without altering the original wood tint.

Preparation

Stir well with a stick before and while applying. Do not shake. Do not apply under sunlight or at a temperature below 10 °C. The wood must be clean and sanded with a 120 grit sandpaper prior to application. The moisture content of the wood must be less than 20%.

It's possible to mix some Colorless Pareo Zero to the colored version in order to decrease the color intensity.

Application

Apply with a brush, a stain pad or a paint roller. If more than 24 hours have passed since the first application, sand lightly with a 120 grit paper before the second application.

The use of a spray gun is highly unsuitable for vertical application. For horizontal surfaces, wipe off any excessive oil after spray gun application.

2 coats of Pareo Zero Colorless or Natural can be applied in order to preserve the wood's original color.

It is not recommended to use Pareo Zero Natural color on exotic woods, torrefied woods or restored woods (stripped and sanded).

Drying Time

- Water resistance: 3 hours
- Between coats: 6 to 18 hours depending on the moisture content of the wood
- Cautious traffic: 12 hours
- Complete drying: 2 days



- Zero solvent
- VOCs under 8 g / L
- Does not blister or whiten over time
- Prevents wood graying while keeping the wood's original tint
- Low environmental impact
- Allows the wood vein to show through
- Easy to refresh: can be reapplied without stripping
- Does not create a film on the wood surface
- Protects against mildew
- Protects against destructive insects

Project Types

- Wall coverings
- Log houses or cabins
- Terraces
- Windows and doors
- Roof shingles
- Outdoor furniture
- Fences
- Woodworks
- Flower boxes
- Children playgrounds

Number of coats

- Horizontal surfaces: 2 coats
- Vertical surfaces: 1 or 2 coats

On horizontal surfaces, always apply 2 coats of the same color to ensure an even wear and easy maintenance.

Coverage

Sanded wood: 100 to 200 sq ft / L

Sawn wood (untreated): 65 to 100 sq ft / L

On torrefied wood : 275 to 375 sq ft / L

On exotic wood : 375 to 450 sq ft / L

Application Tools

Stain applicator, stain pad, paint brush, roller or spray gun.

Maintenance

Clean with Bonito soap and scrub, then rinse well with clear water. When the finish becomes dull and slightly discolored (after 1 to 6 years), clean with Bonito soap, then sand with 120 grit sandpaper, remove dust and apply one coat of Pareo Zero to revive the color and waterproof the wood.

Compatibility

It's strongly recommended reading carefully the technical sheet of the product and making prior test to ensure the propriety and compatibility of the products.

Tool Cleaner

Soapy water

Composition

Modified vegetable oils, water, UV filters, iron oxide.

Storage

Must not freeze. Store in an airtight container at room temperature.

Residues Disposal

Consult your municipality for proper disposal procedure of this product residues.

Warranty

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Prato-Verde products.

Surface Types

- Untreated wood
- Commercial treated dry wood (after 1 year)
- Restored wood (stained or oiled)
- Exotic or torrefied wood

Durability

- Vertical surfaces : 2 to 6 years
- Horizontal surfaces : 1 to 3 years

Sheen

- One coat: Matt (2 to 4%)
- Two coats: Satin Matte (5 to 7%)

VOCs

< 8 g / L

Sizes

- 20 ml (sample)
- 946 ml
- 3.78 L
- 18.9 L

Colors

- 100 - Colorless
- 101 - Natural
- 102 - White
- 103 - Grey
- 104 - Cherry
- 105 - Medium Oak
- 106 - Old pine
- 107 - Burnt wood
- 108 - Chocowood
- 109 - Dark Oak

Origin

Italy