

PAREO RESET

Wood oil and stain stripper

Zero solvents, Zero VOC

Biodegradable and safe for vegetation



Pareo Reset is a biodegradable and vegetation-safe stripper designed for the removal of exterior wood finishes before applying a Prato-Verde product. Pareo Reset works on stained and/or oiled woods, whether clear or semi-clear. It can be used on decks, sidings, fences, and other wooden projects.

Drying Time	12 to 48 hours, depending on temperature and humidity
Available Sizes	946 ml
Applications	Exterior: Ideal for stripping decks, siding, docks, fences, structures, garden furniture, doors, windows, playground equipment, flower boxes, and other outdoor wood projects.
Advantages	Low odor Biodegradable
Dilution	1:1 : Mix 1 L of Pareo Reset with 1 L of warm water.
Coverage	200 ft ² /L
Surface Types	Oiled or stained wood
Composition	Water, sodium hydroxide, sodium metasilicate, 2-ethyl hexanol EO-PO surfactant.
Compatibility	Always perform a preliminary test. Certain wood species may darken when in contact with a stain remover. In such cases, it is recommended to bleach the wood with Pareo Prep after the stripping process.
COV	0 g/L
Origin	Canada
Tools Cleaning	Water
Disposal of accessories and residues	Wipe off any liquid residue before recycling this container. Consult your municipality for proper disposal of any remaining product.
Storage and Shelf Life	Protect from freezing. If the product has been exposed to cold temperatures, allow it to return to room temperature for 24-48 hours before using. Store in an airtight container at a temperature between 10°C and 25°C. The product has a shelf life of 12 months under these conditions.
Guarantee	Guarantee: Prato-Verde guarantees the quality of its products. They conform to the description provided in the technical data sheets and on the labels suitable for the intended use, in accordance with the instructions written by the company. However, since the manufacturer has no control over the circumstances, methods, and conditions of use, this guarantee only covers the high quality of Prato-Verde products.

Technical Specifications Preparation

1. Protect surrounding vegetation by watering it before and after treatment.
2. The product is ineffective on wet surfaces; ensure the surface to be treated remains dry.
3. Add 1 liter of PAREO RESET per liter of warm water and mix.
4. Always perform a test of the product on a small area before use.

Technical Specifications Application

1. Apply the mixture onto the dry surface using a sprayer, floor brush, or paintbrush.
2. Let it sit for 10 to 15 minutes.
3. Reapply the solution if it dries during the waiting time; the surface should remain well saturated with the product.
4. Scrub the surface with a stripping brush and rinse thoroughly with plenty of water OR use a high-pressure water jet (1000 to 3000 psi) to remove the stain. Rinse until all foam is eliminated.
5. Allow the wood to dry completely before repeating the application if necessary or before applying a new finishing product.

Tips

Protect surrounding vegetation by spraying it with water before and after treatment. The product is ineffective on wet surfaces; ensure that the surface to be treated remains dry.

WARNINGS

CORROSIVE

CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS.

Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Use only in a well-ventilated area. Wear a mask, impervious gloves and safety glasses. Handle with care. Close after each use.