

# WOOD STAIN REMOVER

## Wood Stain Remover

Biodegradable and safe for vegetation



Wood Stain Remover is designed for the stripping of exterior wood projects such as decks, siding, fences and other wooden structures. Wood Stain Remover is very effective on most transparent and semi-transparent oils and stains. Wood Stain Remover is biodegradable, VOC-free and safe for vegetation.

Drying Time	12 to 48 hours, depending on temperature and humidity
Available Sizes	3,78 L
Sheen	Matte
Applications	Exterior: Ideal for stripping decks, siding, docks, fences, structures, garden furniture, doors, windows, playground equipment, flower boxes, and other outdoor wood projects.
Surface Types	Oiled or stained wood
Advantages	Low odor Biodegradable
Coverage	200 ft <sup>2</sup> /L
Compatibility	Always perform a preliminary test. Certain wood species may darken when in contact with a stain remover. In such cases, it is recommended to bleach the wood with Pareo Prep after the stripping process.
Composition	Water, sodium hydroxide, sodium metasilicate, 2-Ethyl Hexanol EO-PO surfactant.
COV	0 g/L
Origin	Canada
Tools Cleaning	Water
Disposal of accessories and residues	Wipe off any liquid residue before recycling this container. Consult your municipality for proper disposal of any remaining product.
Storage and Shelf Life	Protect from freezing. If the product has been exposed to cold temperatures, allow it to return to room temperature for 24-48 hours before using. Store in an airtight container at a temperature between 10°C and 25°C. The product has a shelf life of 12 months under these conditions.
Guarantee	Guarantee: Prato-Verde guarantees the quality of its products. They conform to the description provided in the technical data sheets and on the labels suitable for the intended use, in accordance with the instructions written by the company. However, since the manufacturer has no control over the circumstances, methods, and conditions of use, this guarantee only covers the high quality of Prato-Verde products.

### Technical Specifications Preparation

1. Protect surrounding vegetation by watering it before and after treatment.
2. The product is ineffective on wet surfaces; ensure the surface to be treated remains dry.
3. Ready to use.
4. Always perform a test of the product on a small area before use.

### Technical Specifications Application

1. Apply the product directly onto the dry surface to be treated using a sprayer, floor brush, or paintbrush.
2. Allow it to sit for 15 minutes.
3. Ensure the surface remains well soaked with the product during the waiting period; reapply as needed.
4. Scrub the surface using a brush and rinse thoroughly with a large amount of water OR use a high-pressure water jet (1000 to 3000 psi) to remove the stain. Rinse completely until all foam is eliminated.
5. Allow the surface to dry completely and repeat the application if necessary or apply a new coating.

### Tips

Protect surrounding vegetation by spraying it with water before and after treatment. The product is ineffective on wet surfaces; ensure that the surface to be treated remains dry.

### WARNINGS

**CORROSIVE**

**CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS.**

Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Use only in a well-ventilated area. Wear a mask, impervious gloves and safety glasses. Handle with care. Close after each use.